

SPEC	SERIES	INTERNATIONAL				
		BX 1 INT'L	BX 2 INT'L	BX 4 INT'L	RM 8 INT'L	RM 16 INT'L
		BX 1 INT'L UK	BX 2 INT'L UK	BX 4 INT'L UK	RM 8 INT'L UK	RM 16 INT'L UK
		BX 1 INT'L GER	BX 2 INT'L GER	BX 4 INT'L GER	RM 8 INT'L GER	RM 16 INT'L GER
Input Voltage and Frequency	230 or 240VAC Range $\pm 10\%$ , (47-63)Hz.					
Input Current Limiting	1.25A 2 X Fuses Rear Panel	2.5A 2 X Fuses Rear Panel	5A 2 X Fuses Rear Panel	8A Circuit Breaker Front Panel	16A Circuit Breaker Front Panel	
Input (inlet) connector Rear panel	IEC 10A Inlet	IEC 10A Inlet	IEC 10A Inlet	IEC 10A Inlet	IEC 16A Inlet	
Line Cord (Included) (See Table)	Type C N/A N/A	Type C N/A N/A	Type C N/A N/A	Type C N/A N/A	Type C N/A N/A	
Input current rating (See Note A)	1.25A	2.5A	5A	8A	16A	
Output voltage	230-240 VAC	230-240 VAC	230-240 VAC	230-240 VAC	230-240 VAC	
Output Current Limiting	N/A	N/A	N/A	N/A	N/A	
Output connector (rear panel)	IEC 10A, 4 Outlets	IEC 10A, 6 Outlets	IEC 10A, 8 Outlets	IEC 10A, 10 Outlets	IEC 16A, 4 Outlets IEC 10A, 8 Outlets	
	UK 13A/250, 1 Outlet	UK 13A/250, 2 Outlet	UK 13A/250, 4 Outlet	UK 13A/250, 5 Outlet	UK 13A/250, 6 Outlet	
	Continental European 16A/250V, 1 Outlet	Continental European 16A/250V, 2 Outlet	Continental European 16A/250V, 4 Outlet	Continental European 16A/250V, 5 Outlet	Continental European 16A/250V, 6 Outlet	
Weight	18.7 lbs (8.5Kg)	24.2 lbs (11Kg)	55 lbs (25Kg)	75 lbs (34Kg)	99 lbs (45Kg)	
Size (w x d x h) (inch) (mm) (See Note B)	6.7 x 9.7 x 4.5 (170 x 246 x 114)	9.5 x 12.6 x 5.9 (241 x 320 x 150)	12.2 x 15.3 x 6.6 (310 x 389 x 168)	19 x 15.5 x 5.2 (483 x 394 x 133)	19 x 18 x 7 (483 x 457 x 179)	