

SERIES SPEC	CUSTOM INSTALL RACK MOUNT 240V					
	RM 15 BAL	RM 20 BAL	RM 45 BAL	RM 60 BAL	RM 75 BAL	RM 100 BAL
Input Voltage and Frequency	Selectable 240VAC (2 x 120VAC, Balanced) or 208VAC. Factory wired for 240VAC. Selectable: 208VAC Range \pm 10%, (57-63)Hz. (See Note C)					
Input Current Limiting	8A Circuit Breaker Front Panel	10A Circuit Breaker Front Panel	25A 2 X Fuses Rear Panel	30A 2 X Fuses Rear Panel	40A 2 X Fuses Internal	50A 2 X Fuses Internal
Input (inlet) connector Rear panel	20A Inlet	20A Inlet	Twist-Lock 2 Pole 3 Wire grounding 30A, 250V NEMA L6-30P	Twist-Lock 2 Pole 3 Wire grounding 30A, 250V NEMA L6-30P	Twist-Lock 2 Pole 3 Wire grounding 50A, 250V	Twist-Lock 2 Pole 3 Wire grounding 50A, 250V
Line Cord (Included) (See Table)	Type C	Type C or B	Type E	Type E	Type F	Type F
Input current rating (See Note A)	8A	10A	20A	24A	32A	40A
Output voltage	120VAC	120VAC	120VAC	120VAC	120VAC	120VAC
Output Current Limiting	N/A	N/A	16A 3 X Circuit Breaker Front Panel	20A 3 X Circuit Breaker Front Panel	16A 5 X Circuit Breaker Front Panel	20A 5 X Circuit Breaker Front Panel
Output connector (rear panel)	Medical Grade Duplex 15A (Qty 5) 10 Outlets	Medical Grade Duplex 20A (Qty 5) 10 Outlets	Medical Grade Duplex 15A (Qty 9) 18 Outlets	Medical Grade Duplex 20A (Qty 9) 18 Outlets	Medical Grade Duplex 15A (Qty 12) 24 Outlets	Medical Grade Duplex 20A (Qty 12) 24 Outlets
Weight	77 lbs (35Kg)	89 lbs (40.5Kg)	131 lbs (59.5Kg)	155 lbs (70.5Kg)	188 lbs (85.6Kg)	220 lbs (100Kg)
Size (w x d x h) (inch) (mm) (See Note B)	19 x 17 x 6.25 (483 x 432 x 159)	19 x 17 x 6.25 (483 x 432 x 159)	19 x 22 x 8 (483 x 559 x 203)	19 x 22 x 8 (483 x 559 x 203)	19 x 23 x 9.75 (483 x 584 x 248)	19 x 23 x 9.75 (483 x 584 x 248)