

SPEC	SERIES			
	CUSTOM WALL MOUNT			
	WM 100 BAL	WM 75 BAL	WM 60 BAL	WM 45 BAL
Input Voltage and Frequency	Selectable 240VAC (2 x 120VAC, Balanced) or 208VAC. Factory wired for 240VAC. Selectable: 208VAC Range $\pm 10\%$, (57-63)Hz. (See Note C)			
Input Current Limiting	50A 2 X Fuses Internal	40A 2 X Fuses Internal	30A 2 X Fuses Internal	25A 2 X Fuses Internal
Input (inlet) connector Rear panel	N/A	N/A	N/A	N/A
Line Cord (Included) (See Table)	N/A	N/A	N/A	N/A
Input current rating (See Note A)	40A	32A	24A	20A
Output voltage	120VAC	120VAC	120VAC	120VAC
Output Current Limiting	20A 5 X Circuit Breaker Internal	16A 5 X Circuit Breaker Internal	20A 3 X Circuit Breaker Internal	16A 3 X Circuit Breaker Internal
Output connector (rear panel)	N/A	N/A	N/A	N/A
Weight	228 lbs (103.6Kg)	203 lbs (92.2Kg)	165 lbs (74.9Kg)	145 lbs (65.8Kg)
Size (w x d x h) (inch) (mm) (See Note B)	27 x 20.5 x 10.5 (686 x 521 x 267)	27 x 20.5 x 10.5 (686 x 521 x 267)	27 x 20.5 x 10.5 (686 x 521 x 267)	27 x 20.5 x 10.5 (686 x 521 x 267)